



Series

OTH3000

Non Programmable Electronic Thermostat





CSA-C828-13 Performance Standard

ICES-003 Standard Compliant

Features

Type Color Voltage

Rating

Control

Temperature range **Display**

Other features

Installation **Application** Warranty

- Non programmable electronic proportional pulsing line voltage thermostat.

- Standard: white.

- 120/208/240V, 50/60 Hz.

- Maximum load: 11.5A at 120/208/240V.

- Minimum load: 1.25A at 120/208/240V.

- 10-minute or 15-second cycle.

- Resolution: 0.5 °C (1 °F).

- Precision: ± 0.15 °C (0.27 °F) on 15-second cycle. - Precision: ± 0.5 °C (0.1 °F) on 10-minute cycle.

- 5 °C (41 °F) to 30 °C (86 °F).

- Digital screen with white LED backlit.

- Display fan-forced heater mode and keypad lock (when activated).

- Choice of temperature display format (°C or °F).

- Temperature setpoints recorded permanently in case of a power outage.

- Ability to set minimum and maximum setpoints.

- Night light mode for the display LED.


- 2-wire thermostat, easy to install.


- Baseboard heater, radiant ceiling, radiant floor and fan-forced convector.

- 3-year warranty against defects.



Approval Drawings





Model

Product #	Description	Volts	Watts	Qty
OTH3000	Non programmable electronic proportional pulsing line thermostat	120/208/240	1380/2390/300	

Standard color is white.

Specifications may change without prior notice

Project:		
Consultant Engineer:		
Electrician Contractor:		
Distributor:	Approval	
Date:	Information	
Contact in Factory:		
Comments:		