

# HEAT TRACE

## Thermostats & Controllers



**PART NUMBER:**  
HTTS-A  
HTTS-L

**DESCRIPTION:** Mechanical thermostat

- 22 amp switching current SPDT, 120/250/480 V
- Non-hazardous area
- HTTS-A: ambient sensing
- HTTS-L: line sensing



**PART NUMBER:**  
HTTS-EPA  
HTTS-EPL

**DESCRIPTION:** Mechanical thermostat

- 22 amp switching current SPDT, 120/250/480 V
- Class I, Division 1 and 2, Group B,C,D
- HTTS-EPA: ambient sensing
- HTTS-EPL: line sensing



**PART NUMBER:**  
1023953

**DESCRIPTION:** Single Stage Heavy duty Thermostat

- Liquid filled sensing element with snap-acting contacts
- Range: -300 to 1000 F
- Differential: 3 to 120 F between stages
- Bulb Dimensions: 3/8" x 4"
- Capillary Length: 8"
- Resistive Rating: 22 amps, 120 to 277 volts



**PART NUMBER:**  
HTCTRLR-1  
HTCTRLR-2

**DESCRIPTION:** Heat trace microprocessor temperature controller

- 30 amp switching current SSR, 85-280 V
- Class I, Division 2, Group B,C,D
- Ground fault current alarm and trip
- Alarm and communication capabilities
- Single (-1) and dual circuit (-2)



**PART NUMBER:**  
HTCTRLUNIT-5  
HTCTRLUNIT-10  
HTCTRLRUNIT-X

**DESCRIPTION:** Master Trace multi-circuit temperature control panel

- 30 amp switching current SSR, 280 V max
- Class I, Division 2, Group A,B,C,D
- Ground fault current alarm and trip
- Alarm and communication capabilities
- 5 circuit (-5), 10 circuit (-10), custom circuit quantity (-X)



**PART NUMBER:**  
HTRTD-25

**DESCRIPTION:** Armored RTD cable and cord grip with 25' leads