iHEAT TUBING



Product Configuration

IHT 1 E Indeeco **iHEATTUBE** Number of **Process Tubes** Single Tube - exact & continuous length Dual Tube - exact & continuous length Other (*Contact Factory)

Type of Tracer

- Electric (ETBL, ETBM, ETBH)
- Steam (LTB, HTB)
- No Tracer, Pre-Insulated (STB)
- No Tracer, No Insulation, Jacket Only (JTB)

- 38

Α

S

Process Tube Material

Alloy 825 ASTM B-163

Ultra High Purity Tube

Other (*Contact Factory)

PFA ASTM D-3307

316/316L Stainless Steel Seamless ASTM A-269/A-213

- 5M1

-P

Options

- Closed Cell Foam Insulation
 - Random lengths
- (100 ft min.)
- Other (*Contact Factory)

R

Process Tube Wall thickness

- 0.035
- 0.040"
- 0.049"
- 0.062"
- 0.065*
- Other (*Contact Factory)

Jacket Material

- PVC Black
- TPU Black
- TPU (Color other than black)
- Other (*Contact Factory)

Process Tube OD

- 18 1/8"
- 14 1/4"
- 3/8 38
- 12 1/2."
- 34 3/4"
- Other (*Contact Factory)

Type of Trace

N	No Trace
STH	Heavy Steam 3/8 x .035 SS Seamless
STL	Light Steam 3/8 x .035 SS Seamless
5L1	5 watt/foot 120V TPE LSR- Electric
5L2	5 watt/foot 208-277V TPE LSR- Electric
10L1	10 watt/foot 120V TPE LSR - Electric
10L2	10 watt/foot 208-277V TPE LSR - Electric
5M1	5 watt/foot 120V FEP MSR- Electric
5M2	5 watt/foot 208-277V FEP MSR - Electric
10M1	10 watt/foot 120V FEP MSR - Electric
10M2	10 watt/foot 208-277V FEP MSR - Electric

15M1 15 watt/foot 120V FEP MSR - Electric 15M2 15 watt/foot 208-277V FEP MSR - Electric 5 watt/foot 120V FEP HSR - Electric 5 watt/foot 208-277V FEP HSR - Electric 10 watt/foot 120V FEP HSR - Electric 10H2 10 watt/foot 208-277V FEP HSR - Electric 15 watt/foot 120V FEP HSR - Electric 15H2 15 watt/foot 208-277V FEP HSR - Electric 20H1 20 watt/foot 120V FEP HSR - Electric 20H2 20 watt/foot 208-277V FEP HSR - Electric

Other (*Contact Factory)



Indeeco now has a complete line of Electric **Heat Trace Products**

https://indeeco.com/products/heattrace